

## MODEL 7010C



## High Voltage Capacitance Bridge

- Automatic Self Balancing
- Current Comparator Technology
- 2-3 Terminal Measurements
- Lead Compensation Circuit
- Overall Accuracy 15 ppm
- Range Extension Option with 7020

## MODEL INFORMATION

The Model 7010C offers a wider capacitance range and increased voltage sensitivity. Minimum voltage sensitivity for full scale accuracy is 100 volts. The 7010C is a microprocessor controlled, metrology based, high voltage capacitance bridge. Its operation is fully automatic. A large vacuum florescent display presents relevant measuring quantities such as capacitance (Cx) and dissipation factor (Tan $\delta$ ). Easy to use front panel keyboard menus allow the operator to select the number of readings for statistical analysis of uncertainty calculations at the 95% (2s) level. All measured parameters can be transmitted over the IEEE488 interface for storage to a computer.

The model 7010C is a capacitance bridge with a ratio of 1000:1 making it ideal for both low and high voltage applications. The automatic self-balancing feature facilitates the use of the bridge for accurate load loss measurements of

large high voltage inductive loads.

The 7010C may also be used for calibration of precision standard capacitors, tan-delta measurements and of precision potential transformers. Overall accuracy is <15 ppm in magnitude and phase. The technology is based on the two-stage-current-comparator-principle.

The 7010C has a capacitance ratio up to 1000:1 and dissipation (loss tangent) of 0 to 10% with a resolution of 1 ppm. To accommodate capacitance ratios larger than 1000:1 an additional two stage range extender, model 7020, may be added to increase the ratio to 2,000,000:1. All connections are made on the rear of the instrument. The model 7010C is fully protected against transients.

The effect of lead and winding impedance on the measurement accuracy has been reduced by means of a built-in lead compensation circuit.

>163,65546 67810,7 20337 977  
 >198,65546 65612,23 2829 9555  
 >198,65546 65612,23 2829 95556  
 >152,698016 68818,28 2399 92356  
 >198,643636 78617,73 2289 783 56  
 >124,634546 78672,23 7779 683 56  
 >458,11142 83417,73 2397 876 56  
 >145,523286 64486,22 2889 988 56  
 >140,77060 32814,07 7060 328 56



**Applications:**

Shunt Reactor Loss Measurements	Power Transformer Measurements
Calibration of Potential Transformers	Calibration of Low Voltage Std. Capacitors
Calibration of High Voltage Dividers	Calibration of High Voltage Power Capacitors
Inductance Measurements	Measurement of Low Loss, High Voltage Power
Loss Tangent Measurements to 10%	Corona Loss Measurements
<b>Insulator and Dielectric Testing</b>	

**Specifications:**

Capacitance Range	Cs: 10pF to 10,000pF Cx: 10pF to 10,000,000pF (10µF)
Capacitive Ratio 1:1 to 1000:1	Ns: 0 to 1.11110 in steps of 0.000001 Nx: 1 to 1000 in steps of 1, 2, 5
Primary Current	10 Amp Maximum
Secondary (Cs) Current Range	40µA to 10mA
Dissipation Factor Range	0 to 10% in steps of 0.000001
Inductance Range	700µH to 700000H (Q factor > 10)
Test Frequencies	50 and 60Hz
Accuracy	Ratio: ±15 ppm for all Cx Ratios
Loss Angle	±1% of Reading ±10 ppm
Display	Large Vacuum Florescent
Reading Update	1 Second
Warm Up Time	< 5 Minutes to Full Rated Accuracy
Operating Environment	18 to 34°C, 10 to 80% RH
Operating Power	100, 120, 220, 240V - 50/60Hz

**Product Details**

Dimensions	545 x 435 x 355 mm
Weight	41 kg
Shipping Weight	50 kg
Warranty	1 Year Parts & Labor

Form MI 66, Rev. 8, Dated 2012-03-28 (QAP19, App. "N")

Data Subject to Change - Rev. 0

**Corporate Headquarters**

**Measurements International**  
 PO Box 2359, 118 Commerce Drive  
 Prescott, Ontario, Canada K0E 1T0  
 Phone: (613) 925-5934  
 Fax: (613) 925-1195  
 Email: sales@mintl.com  
 Toll Free: 1-800-324-4988

**Worldwide Offices**

**MI-USA**  
 Phone: (407) 706-0328  
 Fax: (407) 706-0318  
 Email: sales@mintl.com  
 Toll Free: 1-866-684-6393

**MI-China**  
 Phone: 86-10-64459890  
 Fax: 86-10-64459871  
 Email: sales@mintl.com

**MI-Europe**  
 Phone: (420) 731-440-663  
 Fax: (420) 572-572-358  
 Email: sales@mintl.com



[www.mintl.com](http://www.mintl.com)