

30 to 700°C

Dry Block Calibrator

510 Medusa & 511 Medusa 3

- 45 x 285mm Calibration Volume
- Use for Comparison and Fixed Point Calibration
- Use with very long thermometers

Isotech have a wide range of Dry Blocks to suit probes requiring a large immersion depth. These products feature large and deep calibration volumes. As such they are less portable than the earlier Dry Blocks, but have higher capacities and retain outstanding temperature uniformity, this uniformity is so good that these larger products are also apparatus for Secondary Laboratories to realize the Fixed Points of ITS-90.

Medusa 510 has a maximum operating temperature of 550°C. The Medusa Model 511 can be used to 700°C and features three zone control. In addition to the main heating zone there are additional top and bottom heaters which compensate for the end losses creating a constant temperature zone across the well.

For Comparison Calibration the Medusa should be used with an insert, the standard insert has six 8mm pockets 250mm deep. Also available is an insert 44mm diameter x 170mm deep which is suspended from the top of the block so that the height is user adjustable. For flexibility the Medusa can also be used with accessories for infrared thermometers and surface sensors. The Medusa is available in two models, the BASIC (B) and the SITE (S). The B model includes a sophisticated temperature controller with a dual display for Set Temperature and Dry Block Temperature.

The S model includes a built-in digital thermometer to which an external standard thermometer can be connected giving greater accuracy, eliminating temperature gradient and loading errors. Also included in the site model is a timer which can set the bath between two temperatures, and automate ITS-90 fixed point operation. For Surface Sensor and Blackbody use an external thermometer is recommended. For laboratory accuracy the Medusa can be used with a high-end temperature indicator such as an Isotech TTI model.

Includes as standard: Windows Software, Computer Interface and a Ramp to Set Point Feature. Increased resolution of ± 0.01 available throughout the range via the PC interface and from 0.01 to +99.99 locally on the auto-ranging front display. The controller features multi-point block to display correction giving good absolute accuracy.

The S model has universal sensor input allowing Platinum Resistance Thermometers, Thermocouples (types K, N, R, S, L, B, PL2, T, J and E) along with Linear Process Inputs including 4-20mA current transmitters to be displayed on the in-built indicator. The indicator can be programmed with up to five calibration points to provide high accuracy digital probe matching. The indicator and controller are both addressable over the communications link.



Fixed Point Cells Available


Material	Temperature
Gallium	29.7646°C
Indium	156.5985°C
Tin	231.928°C
Zinc	419.527°C
Aluminium	660.323°C

Specification

Model	510 Medusa	511 Medusa 3
Temperature Range	30°C to 550°C	50°C to 700°C
Absolute stability over 30 minutes	Metal Block Bath Blackbody Source Surface Sensor Calibrator ITS-90 Fixed Point	±0.03°C ±0.1°C ±0.5°C ±0.001°C
Computer Interface	Included with Software	
Cools from	550°C to 30°C in 5 hours	
Heats from	30°C to 550°C in 90 minutes	
Uncertainties	Refer to Uncertainties Graph	
Calibration volume	45mm diameter by 285mm deep	
Standard Insert	Six 8mm pockets all 250mm deep	
Display Resolution	(0.01) to 99.99 (0.1) 100.0 to 650.0 PC can display 0.01 across whole range with the software included	
Indicator units	°C, °F, K	
Power	108 to 130V or 208 to 240V 1000 Watts	50 / 60Hz 1800 Watts
Overall dimensions	Height 430mm Width 310mm Depth 300mm	
Weight	17kg	25kg

Performance and Use

510 Medusa



Calibration and Uncertainty

A certificate, traceable to National Standards, is included as standard. Recommended is an optional UKAS five-point calibration.

The accuracy of the Medusa will depend very much on the mode of use, see the Uncertainty Graph for typical uncertainties. NTPL calculate the uncertainties to UKAS requirements. The Medusa meets the Calibration Capacity requirements of EA-10/13, "EA Guidelines on the Calibration of Temperature Block Calibrators."

Features (Basic & Site)

Dry Block
Surface Sensor Option
Infrared Calibration Option
ITS-90 Fixed Point Cells
Additional 8mm Pre-heat Pocket
Configurable Units: °C, °F and K
Supply Voltage Power Correction

Medusa

✓
✓
✓
✓
✓
✓
✓

Additional Features (Site)

Independant Temperature indicator
Universal Input Types PT100
Thermocouples Types K,N,R,S,L,PL2,T,J,E
Linear Process Inputs Including 4-20 mA
Stand Alone Thermostat Testing
Thermostat Testing With PC
Five Point Digital Probe Matching

Medusa

✓
✓
✓
✓
✓
✓
✓

510 Medusa & 511 Medusa 3


Calibrate all sensor types - Thermocouples, PRT's, Thermistors, Thermostats, Infrared, Surface Sensors...



510 Metal Block Insert

- 510-06-01** Standard Insert included
- 510-06-02** Blank Insert without pockets for local machining

- 510-06-03** Special Insert. Contact Isotech with your requirements



- 510-06-04** Adjustable Equalising Block

511 Metal Block Insert

- 511-06-01** Standard Insert Included

- 511-06-02** Blank Insert without pockets for local machining

- 511-06-03** Special Insert. Contact Isotech with your requirements

- 511-06-04** Adjustable Equalising Block



Blackbody Kit

- 510-06-05** For 510. Includes a Blackbody target and Sensor.

- 511-06-05** For 511. Includes a Blackbody target and Sensor.




510 Surface Sensor Calibration with Surface Sensor Kit

- 510-06-06** Includes an insert and an angled thermocouple.

511 Surface Sensor Calibration with Surface Sensor Kit

- 511-06-06** Includes an insert and an angled thermocouple.



ITS-90 Fixed Point Cells

- ITL17401M** Gallium Slim Cell (510)
- ITL17668ML** Indium Slim Cell
- ITL17669ML** Tin Slim Cell
- ITL17671ML** Zinc Slim Cell
- ITL17672ML** Slim Aluminium Cell (511)
- 510-05-00** Cell Basket for 510
- 510-05-01** Cell Basket for 511



UKAS Calibration

UKAS Calibration available to order, legally traceable in more than 70 countries.



Standard Probe

- 935-14-95H/DB** Platinum Resistance Thermometer for use up to 650°C.



Carrying Case

- 931-22-58** Sturdy case accommodates the unit with room for accessories

How To Order

Specify Model, Basic or Site, Supply Voltage, Accessories and if UKAS Calibration is required.