



STANDARD RESISTOR OIL BATH

- Peltier Cooled
- DC Stirrer Motors for Low Electrical Noise
- Dual Drain Ports
- Adjustable Stir Speed
- 10-Channel Interface Panel
- 2-Stage Temperature Band Protection
- Free Standing Bench Height
- Compatible with MI Bridge Software
- Grounded Stainless Steel Tank

MODEL 9400



MODEL 9400 STANDARD RESISTOR OIL BATH

Measurements International's series of fluid baths are used for the maintenance of standard resistors and shunts. The 9400 has been designed after compiling years of customer feedback on existing resistor oil baths.

The result is a stable, quiet oil bath that can be used with the CCC and QHR due to its low electrical noise and low operating and maintenance costs.

The improved 9400 utilizes brushless DC stirrer motors to further reduce electrical noise and improve the chambers' fluid flow in order to reduce the temperature gradient. This new design avoids "temperature shadows," where the heat dissipated from one resistor will directly affect "downstream" resistors.



The 9400 does not use a compressor and as such is very quiet both audibly and electrically. The one-piece stainless steel tank is grounded and isolated from the anodized resistor shelf. Stirring is provided by two adjustable speed motors. The tank lid is insulated and sits atop a resistor drain shelf. The access opening is 25" by 8" to accommodate easy access for handling larger resistors.

The touch screen interface displays temperature and gives the user access to the PID for adjustment of set points, alarm settings and stirring speed. The exclusive design uses a proprietary temperature band protection circuit.

The bath is equipped with two drain/fill ports.

There are two 2" vertical conduit ports to for resistor cables and to minimize wicking. These ports allow the tank lid to remain in place for increased temperature stability. For connections to resistors and shunts, the standard interconnect panel provides a simple and easy way to connect to external instrumentation without having to remove the tank lid and touching the oil.

The 9400 comes standard with IEEE-488 and serial RS232 interface and can be controlled via Measurements International's resistance bridge operating software.





MODEL 9400 STANDARD RESISTOR OIL BATH

Specifications: Rev 8

Operating	
Stability	< 0.002 °C
Operating Temperature	15 – 30 °C
Maximum Temperature Gradient	0.1 °C
Size	
Tank Size	686 × 368 × 356 mm
Tank Opening	635 × 203 mm
Usable Tank Area	686 × 279 × 330 mm
Fluid	
Mineral Oil / Water	70 to 80 Litres
Controller	
Input	4 W RTD
Control	Heat/Cool
Control	Loop PID
Safety	
Level One	Main Controller
Redundant	High/Low with Sensor

Dimensions (L × W × H):
 876 × 572 × 1384 (mm)

Weight:
 113 kg

Shipping Weight:
 190 kg

Main Power:
 120-240 V @ 50-60 Hz
 2400 VA maximum

Corporate Headquarters
Measurements International
 PO Box 2359, 118 Commerce Drive
 Prescott, Ontario, Canada K0E 1T0
 Phone: 613-925-5934
 Fax: 613-925-1195
 Email: sales@mintl.com
 Toll Free: 1-800-324-4988

Worldwide Offices
MI-USA
 Phone: 407-706-0328
 Email: sales@mintl.com

MI-Europe
 Phone: +(420) 731-440-663
 Email: sales@mintl.com

MI-India
 Phone: +(91) 98 10 134 932
 Email: sales@MILLP.co.in

MI-China
 Phone: +(86) 10-64459890
 Email: sales@mintl.com

MI-Japan
 Phone: +(81) 72 39 64 660
 Email: kaz@mijpn.com



www.mintl.com